



YOUR SOURCE FOR POWER & MAGNETICS

CALL: 508-580-8515, EXT 1

FAX: 508-580-8511

WWW.INTERNATIONALCOIL.COM

INTERNATIONAL COIL, INC.

CATALOG:


MAGNETICS

INDUCTORS, TRANSFORMERS, BOBBINS


Consult factory for pricing and lead-time

sales@internationalcoil.com

| TABLE OF CONTENTS: MAGNETICS | |
|-------------------------------------|-------------------------------------------------------------|
| Page 3 | ICI68T INDUCTOR SERIES |
| Page 4 & 5 | ICI83T INDUCTOR SERIES |
| Page 6 | ICI84T INDUCTOR AND TRANSFORMER SERIES |
| | ICI86T THT CURRENT SENSE TRANSFORMERS |
| Page 7 | ICI89T LOW COST SERIES INDUCTORS |
| | ICI96T SERIES HIGH AND LOW CURRENT COUPLED INDUCTORS |
| Page 8 | ICI97T SERIES SURFACE MOUNT INDUCTORS SELF-LEADED |
| Page 9 | ICI98T SERIES HIGH AND LOW CURRENT COUPLED INDUCTORS |
| | ICI-99T INDUCTOR for HARRIS SEMI-CONDUCTOR |
| | ICI25EE SERIES COMMON MODE LINE FILTER |
| Page 10 | ICIBI-1 SERIES BOBBIN TYPE INDUCTORS |
| Page 11 | ICIBI-2 SERIES BOBBIN TYPE INDUCTORS |
| Page 12 | ICIBI-3 SERIES BOBBIN TYPE INDUCTORS |
| Page 13 | ICIBI-4 SERIES BOBBIN TYPE INDUCTORS |
| | |

| INDUCTORS AND TRANSFORMERS FROM INTERNATIONAL COIL, INC. | | | | | | | | | | |
|-----------------------------------------------------------------------------------------------------------------|--------------------------|------|------|-----------------------------|-----------------------------|------------------------------------|------------------|----------------|-------------|----------------|
| Part Number | Rated RMS Current (Amps) | 117V | 220V | Inductance at 1KHz (mH MIN) | Test Level Volts RMA 1.0KHz | Leakage Inductance 130KHz (uH MIN) | DCR Max.each WDG | Package Number | Low Profile | Vertical Mount |
| ICI68T INDUCTOR SERIES  | | | | | | | | | | |
| ICI68T1031V | 1.8 | 210 | 420 | 10 | 0.5 | 130 | 0.24 | 1 | 0.032 | 0.032 |
| ICI68T1031V | 1.8 | 210 | 420 | 10 | 0.5 | 130 | 0.24 | 1 | 0.032 | 0.032 |
| ICI68T3021V | 3.5 | 400 | 800 | 3 | 0.2 | 35 | 0.06 | 1 | 0.032 | 0.032 |
| ICI68T1021V | 6 | 700 | 1400 | 1 | 0.08 | 12 | 0.02 | 1 | 0.036 | 0.036 |
| ICI68T1632V | 2.6 | 300 | 600 | 16 | 1 | 180 | 0.16 | 2 | 0.032 | 0.04 |
| ICI68T8022V | 3.2 | 375 | 750 | 8 | 0.5 | 90 | 0.12 | 2 | 0.032 | 0.04 |
| ICI68T4022V | 5.2 | 600 | 1200 | 4 | 0.2 | 45 | 0.04 | 2 | 0.036 | 0.036 |
| ICI68T2022V | 7.5 | 875 | 1750 | 2 | 0.08 | 25 | 0.02 | 2 | 0.047 | 0.047 |


INDUCTORS AND TRANSFORMERS FROM INTERNATIONAL COIL, INC.


| THT Part Number | SMT Part Number | In Circuit Operating Parameters | | | Nominal DCR | Package | |
|-----------------------------------------------------------------------------------------------------------------|-----------------|---------------------------------|--------------------------|-----------------|-------------|--------------|---------------|
| | | Nominal Inductance | Rated Current Amps DC | Max Etop V=uSec | | Through Hole | Surface Mount |
| ICI83T INDUCTOR SERIES  | | | | | | | |
| ICI83T-259P2 | ICI83T-259L2 | 259 | 0.13 | 23.1 | 3.4 | P2 | L2 |
| ICI83T-178P2 | ICI83T-178L2 | 178 | 0.16 | 16.5 | 2.8 | P2 | L2 |
| ICI83T-118P2 | ICI83T-118L2 | 118 | 0.2 | 13.2 | 1.8 | P2 | L2 |
| ICI83T-790P2 | ICI83T-790L2 | 79 | 0.25 | 9.9 | 1.5 | P2 | L2 |
| ICI83T-550P2 | ICI83T-550L2 | 55 | 0.3 | 6.6 | 1 | P2 | L2 |
| ICI83T-390P2 | ICI83T-390L2 | 39 | 0.34 | 6.6 | 0.8 | P2 | L2 |
| ICI83T-260P2 | ICI83T-260L2 | 26 | 0.45 | 6.6 | 0.62 | P2 | L2 |
| ICI83T-374P3 | ICI83T-374L3 | 374 | 0.2 | 75.9 | 2.7 | P3 | L3 |
| ICI83T-256P3 | ICI83T-256L3 | 256 | 0.25 | 33 | 2.2 | P3 | L3 |
| ICI83T-176P3 | ICI83T-176L3 | 176 | 0.3 | 26.4 | 1.4 | P3 | L3 |
| ICI83T-118P3 | ICI83T-118L3 | 118 | 0.38 | 19.8 | 1.2 | P3 | L3 |
| ICI83T-780P3 | ICI83T-780L3 | 78 | 0.46 | 16.5 | 0.8 | P3 | L3 |
| ICI83T-550P3 | ICI83T-550L3 | 55 | 0.56 | 13.2 | 0.5 | P3 | L3 |
| ICI83T-390P3 | ICI83T-390L3 | 39 | 0.68 | 9.9 | 0.3 | P3 | L3 |
| ICI83T-260P3 | ICI83T-260L3 | 26 | 0.84 | 6.6 | 0.2 | P3 | L3 |
| ICI83T-170P3 | ICI83T-170L3 | 17 | 1.02 | 6.6 | 0.1 | P3 | L3 |
| ICI83T-375P7 | ICI83T-375L7 | 375 | 0.36 | 75.9 | 1.3 | P7 | L7 |
| ICI83T-251P7 | ICI83T-252L7 | 252 | 0.44 | 49.5 | 0.9 | P7 | L7 |
| ICI83T-171P7 | ICI83T-173L7 | 173 | 0.54 | 36.3 | 0.6 | P7 | L7 |
| ICI83T-115P7 | ICI83T-115L7 | 115 | 0.67 | 29.7 | 0.4 | P7 | L7 |
| ICI83T-780P7 | ICI83T-780L7 | 78 | 0.82 | 23.1 | 0.3 | P7 | L7 |
| ICI83T-540P7 | ICI83T-540L7 | 54 | 1 | 16.5 | 0.2 | P7 | L7 |
| ICI83T-380P7 | ICI83T-380L7 | 38 | 1.2 | 13.2 | 0.1 | P7 | L7 |
| ICI83T-260P7 | ICI83T-260L7 | 26 | 1.48 | 9.9 | 0.1 | P7 | L7 |
| ICI83T-180P7 | ICI83T-180L7 | 18 | 1.81 | 9.9 | 0.06 | P4 | L4 |
| ICI83T-377P4 | ICI83T-377L4 | 377 | 0.68 | 75.9 | 1 | P4 | L4 |
| ICI83T-248P4 | ICI83T-248L4 | 248 | 0.83 | 72.6 | 0.6 | P4 | L4 |
| ICI83T-168P4 | ICI83T-168L4 | 168 | 1.02 | 56.1 | 0.4 | P4 | L4 |

INDUCTORS AND TRANSFORMERS FROM INTERNATIONAL COIL, INC.

| THT Part Number | SMT Part Number | In Circuit Operating Parameters | | | Nominal DCR | Package | |
|-----------------|-----------------|---------------------------------|--------------------------|-----------------|-------------|--------------|---------------|
| | | Nominal Inductance | Rated Current Amps DC | Max Etop V=uSec | | Through Hole | Surface Mount |
| ICI83T-111P4 | ICI83T-112L4 | 112 | 1.26 | 42.9 | 0.3 | P4 | L4 |
| ICI83T-770P4 | ICI83T-770L4 | 77 | 1.54 | 33 | 0.2 | P4 | L4 |
| ICI83T-530P4 | ICI83T-530L4 | 53 | 1.87 | 26.4 | 0.13 | P4 | L4 |
| ICI83T-370P4 | ICI83T-370L4 | 37 | 2.24 | 19.8 | 0.1 | P4 | L4 |
| ICI83T-240P4 | ICI83T-240L4 | 24 | 2.74 | 16.5 | 0.07 | P4 | L4 |
| ICI83T-170K1 | ICI83T-170L4 | 17 | 3 | 13.2 | 0.05 | K1 | L4 |
| ICI83T-251K3 | ICI83T-251H6 | 250 | 1.5 | 72.6 | 0.23 | K3 | H6 |
| ICI83T-168K3 | ICI83T-168H6 | 168 | 1.81 | 75.9 | 0.18 | K3 | H6 |
| ICI83T-114K3 | ICI83T-114H6 | 114 | 2.22 | 62.7 | 0.1 | K3 | H6 |
| ICI83T-770K3 | ICI83T-770H6 | 77 | 2.7 | 52.8 | 0.09 | K3 | H6 |
| ICI83T-530K3 | ICI83T-530H6 | 53 | 3 | 42.9 | 0.08 | K3 | H6 |
| ICI83T-380K2 | ICI83T-380H6 | 38 | 3 | 29.7 | 0.05 | K3 | H6 |
| ICI83T-250K2 | ICI83T-250L5 | 25 | 3 | 19.8 | 0.04 | K2 | L5 |
| ICI83T-167K4 | | 167 | 2.5 | 75.9 | 0.14 | K4 | |
| ICI83T-111K4 | | 110 | 3 | 75.9 | 0.09 | K4 | |
| ICI83T-770K3 | ICI83T-770H6 | 77 | 3 | 59.4 | 0.08 | K3 | H6 |
| ICI83T-190K3 | | 19 | 4.5 | 32 | 0.02 | K3 | |

INDUCTORS AND TRANSFORMERS FROM INTERNATIONAL COIL, INC.

| Part Number Inductor | Part Number Transformer | RT | Sec.Turns NS | Sec.Inductance | DCR Sec.MAX | DCR PRI | Vs Mv |
|---------------------------------------------------------------------------------------------------------------------------------|-------------------------|------|--------------|----------------|-------------|---------|-------|
| ICI84T INDUCTOR AND TRANSFORMER SERIES  | | | | | | | |
| ICI84T-151A | ICI84T-151B | 1.50 | 10 | 150 | 0.055 | 0.006 | 30 |
| ICI84T-601A | ICI84T-601B | 3.00 | 20 | 600 | 0.097 | 0.006 | 60 |
| ICI84T-402A | ICI84T-402B | 7.50 | 50 | 4000 | 0.24 | 0.006 | 160 |


| Part Number | Turns Ratio | Secondary Inductance | DCR SEC 1 -10 MAX | DCR SEC 1 -10 MAX | DCR SEC 1 -10 MAX | HI-POT/ Vrms | RT | 1pk/Amps | DROOP | Max Flux Density | Kb | Req |
|--------------------------------------------------------------------------------------------------------------------------------|-------------|----------------------|-------------------|-------------------|-------------------|--------------|-----|----------|-------|------------------|--------|------|
| ICI86T THT CURRENT SENSE TRANSFORMERS  | | | | | | | | | | | | |
| ICI86T-763A | 0.044675926 | 76 | 2.8 | 2.15 | 2.15 | 3000 | 200 | 34 | 1 | 2000 | 17.12 | 0.9 |
| ICI86T-193A | 0.043518519 | 19 | 1.4 | 2.15 | 2.15 | 3000 | 100 | 35 | 1.98 | 2000 | 68.49 | 0.8 |
| ICI86T-502A | 1:01:50 | 5 | 0.7 | 2.15 | 2.15 | 3000 | 15 | 36 | 1.19 | 2000 | 273.97 | 0.75 |

| Part Number | I AMPS | RT | DROOP % | Ls mH MIN | Rs MAX | YURNS Ns | HIPOT Vrms |
|-------------|--------|----|---------|-----------|--------|----------|------------|
|-------------|--------|----|---------|-----------|--------|----------|------------|

ICI-87T SERIES 500 Khz CURRENT SENSE TRANSFORMERS AND INDUCTORS 

| | | | | | | | |
|-----------------|------|-----|-----|-------|------|-----|-----|
| ICI87T-382C3/T4 | 15.3 | 25 | 1.3 | 3.8 | 0.38 | 50 | 500 |
| ICI87T-142C3/T4 | 16.3 | 50 | 0.7 | 14.8 | 0.93 | 100 | 500 |
| ICI87T-592C3/T4 | 16.4 | 100 | 0.3 | 59.2* | 3.9 | 200 | 500 |

INDUCTORS AND TRANSFORMERS FROM INTERNATIONAL COIL, INC.

| Low Profile Part Number | Vertical Part Number | Inductance Typical (uH) | Idc amps | Etop (vusec) | Energy Storage | Inductance No dc±20% | 20KHZ Test mv No dc | Dcr Max | Coil Size Code | K Mount Part Number | Lead Diameter |
|---------------------------------------------------------------------------------------------------------------------------|----------------------|-------------------------|----------|--------------|----------------|----------------------|---------------------|---------|----------------|---------------------|---------------|
| ICI89T LOW COST SERIES INDUCTORS  | | | | | | | | | | | |
| Not Applicable | ICI89T200VH | 20 | 2 | 52 | 40 | 32.8 | 33 | 0.06 | H | Not Applicable | 0.02 |
| Not Applicable | ICI89T250VA | 25 | 2.6 | 30 | 85 | 20.7 | 22 | 0.043 | A | ICI89T250K1 | 0.02 |
| ICI89T500WB | ICI89T500VB | 50 | 2.6 | 50 | 169 | 45.7 | 45 | 0.071 | B | ICI89T500K2 | 0.02 |
| ICI89T101WC | ICI89T101VC | 100 | 2.6 | 90 | 338 | 94.1 | 90 | 0.1 | C | ICI89T101K3 | 0.02 |
| Not Applicable | ICI89T350VB | 35 | 2.6 | 55 | 118 | 28.4 | 36 | 0.037 | B | ICI89T350K2 | 0.025 |
| ICI89T700WC | ICI89T700VC | 70 | 3 | 85 | 315 | 61 | 73 | 0.052 | C | ICI89T700K3 | 0.025 |
| ICI89T145WD | ICI89T145VD | 145 | 3 | 140 | 653 | 141.8 | 140 | 0.087 | D | ICI89T145K4 | 0.025 |
| Not Applicable | ICI89T285VE | 285 | 3 | 300 | 1283 | 264.1 | 340 | 0.14 | E | ICI89T285K5 | 0.025 |
| Not Applicable | ICI89T451VF | 450 | 3 | 425 | 2025 | 436.3 | 500 | 0.2 | F | Not Applicable | 0.025 |
| ICI89T100WD | ICI89T101VD | 100 | 3.6 | 130 | 648 | 90.7 | 110 | 0.045 | D | ICI89T101K4 | 0.032 |
| Not Applicable | ICI89T165VE | 165 | 4 | 240 | 1320 | 152 | 260 | 0.07 | E | ICI89T165K5 | 0.032 |
| Not Applicable | ICI89T271VF | 270 | 4 | 350 | 2160 | 263.9 | 400 | 0.1 | F | Not Applicable | 0.032 |
| Not Applicable | ICI89T400VC | 40 | 4 | 70 | 320 | 37.9 | 57 | 0.027 | C | ICI89T400K3 | 0.032 |
| Not Applicable | ICI89T200VG | 22 | 5 | 44 | 275 | 20.3 | 37 | 0.02 | G | Not Applicable | 0.032 |
| ICI89T100WE | ICI89T101VE | 100 | 5 | 200 | 1250 | 90.7 | 180 | 0.034 | E | ICI89T101K5 | 0.042 |
| Not Applicable | ICI89T171VF | 170 | 5 | 300 | 2125 | 159.7 | 310 | 0.05 | F | Not Applicable | 0.042 |
| ICI89T550WD | ICI89T550VD | 55 | 5 | 100 | 688 | 54.9 | 88 | 0.023 | D | ICI89T550K4 | 0.042 |
| Not Applicable | ICI89T950VF | 95 | 7 | 225 | 2328 | 96 | 200 | 0.025 | F | Not Applicable | 0.051 |
| ICI89T500WE | ICI89T500VE | 55 | 7 | 150 | 1348 | 49.1 | 100 | 0.017 | E | ICI89T550K5 | 0.051 |
| Not Applicable | ICI89T550VF | 55 | 10 | 175 | 2750 | 55.9 | 120 | 0.013 | F | Not Applicable | |

ICI96T SERIES HIGH AND LOW CURRENT COUPLED INDUCTORS 

| Part Number | 1 DC | L w/DC | ET | Size Code | L w/ODC | Max DCR |
|--------------|------|--------|-------|-----------|---------|---------|
| ICI96T-053I4 | 23.8 | 0.53 | 1 | I4 | 0.88 | 1.7 |
| ICI96T-011I5 | 21 | 1.1 | 1.75 | I5 | 2.1 | 3 |
| ICI96T-021I6 | 22.4 | 2.1 | 3.25 | I6 | 4 | 3.4 |
| ICI96T-430C3 | 1.1 | 43.6 | 7.83 | C3 | 77 | 309 |
| ICI96T-220C4 | 2.7 | 21.9 | 6.9 | C4 | 39.5 | 90.5 |
| ICI96T-040C5 | 6.4 | 4.025 | 3.135 | C5 | 6.575 | 23 |

INDUCTORS AND TRANSFORMERS FROM INTERNATIONAL COIL, INC.

| PART NUMBER | REFERENCE VALUES | | | CONTROL VALUES | | | CALCULATION DATA | | |
|----------------------------------------------------------|------------------|----------------------|------------|----------------|-------------------------|---------|-------------------|-------------|--------|
| | IDC/Amps | L with DC/ LDC uH | ET V-u sec | Package | L w/o DC Lo uH+/-20% | DCR Rdc | 100GAUSS ET100 | 1 Amp DC Hi | DCR Rn |
| ICI97T SERIES SURFACE MOUNT INDUCTORS SELF-LEADED | | | | | | | | | |
| ICI97T-062L2 | 1.4 | 6.2 | 1.33 | L2 | 7 | 70 | 0.94 | 21.9 | 60.3 |
| ICI97T-170L2 | 1 | 17.6 | 2.4 | L2 | 22.7 | 125 | 1.68 | 39.3 | 109 |
| ICI97T-290L3 | 1.4 | 29.7 | 4.6 | L3 | 35.3 | 166 | 4.12 | 23.2 | 141 |
| ICI97T-580L7 | 1.3 | 58.1 | 7.83 | L7 | 73 | 290 | 1.09 | 28.8 | 233 |
| ICI97T-114L3 | 0.94 | 114 | 10 | L3 | 167 | 380 | 8.97 | 50.5 | 330 |
| ICI97T-191L7 | 0.9 | 192 | 15.7 | L7 | 292 | 560 | 14.2 | 57.7 | 472 |
| ICI97T-383L7 | 0.72 | 383 | 23.5 | L7 | 672 | 862 | 21.3 | 86.5 | 750 |
| ICI97T-645L4 | 0.74 | 645 | 36.5 | L4 | 1134 | 1250 | 37.2 | 84.4 | 1040 |
| ICI97T-102L5 | 0.71 | 1070 | 54.4 | L5 | 1950 | 1700 | 56.9 | 95.7 | 1480 |
| ICI97T-010L2 | 3.4 | 1.01 | 0.532 | L2 | 1.1 | 11 | 0.37 | 8.74 | 12.5 |
| ICI97T-094L3 | 2.8 | 9.4 | 2.7 | L3 | 12.3 | 43.4 | 2.42 | 13.7 | 37.8 |
| ICI97T-043L7 | 2.7 | 16.2 | 4.29 | L7 | 21.9 | 63 | 3.88 | 15.8 | 54.7 |
| ICI97T-290L4 | 2.7 | 29.1 | 6.9 | L4 | 40.5 | 85 | 7.02 | 15.9 | 75.8 |
| ICI97T-500L5 | 2.6 | 50 | 10.5 | L5 | 72.9 | 133 | 11 | 18.5 | 115 |
| ICI97T-038L3 | 4.8 | 3.8 | 1.76 | L3 | 5.2 | 17.3 | 1.58 | 8.87 | 14.8 |
| ICI97T-051L7 | 5.4 | 5.1 | 2.51 | L7 | 7.5 | 17.7 | 2.27 | 9.25 | 14.3 |
| ICI97T-090L4 | 5.5 | 9 | 4.06 | L4 | 14 | 22.3 | 4.13 | 9.38 | 19.3 |
| ICI97T-160L5 | 5.1 | 16.1 | 6.27 | L5 | 25.9 | 32 | 6.55 | 11 | 30.3 |
| ICI97T-025L7 | 8 | 2.5 | 1.77 | L7 | 3.8 | 8.3 | 1.61 | 6.53 | 7.2 |
| ICI97T-049L4 | 7.8 | 4.9 | 3.04 | L4 | 7.9 | 12.4 | 3.1 | 7.03 | 10.5 |
| ICI97T-093L5 | 7.2 | 9.3 | 4.92 | L5 | 16 | 18.7 | 5.15 | 8.67 | 16.3 |
| ICI97T-013H7 | 11.5 | 1.32 | 1.33 | H7 | 2.1 | 4 | 1.2 | 4.9 | 3.39 |
| ICI97T-025H4 | 11.4 | 2.5 | 2.23 | H4 | 4.2 | 5.4 | 2.27 | 5.16 | 4.64 |
| ICI97T-047H5 | 10.4 | 4.7 | 3.58 | H5 | 8.4 | 8.3 | 3.75 | 6.3 | 7.18 |
| ICI97T-094H6 | 10.9 | 9.4 | 6.84 | H6 | 17.6 | 12.3 | 7.93 | 6.24 | 10.7 |
| ICI97T-008H7 | 14.3 | 0.81 | 1.035 | H7 | 1.25 | 2.5 | 0.94 | 381 | 2.16 |
| ICI97T-016H4 | 13.9 | 1.68 | 1.83 | H4 | 2.8 | 3.6 | 1.86 | 4.22 | 3.16 |
| ICI97T-035H5 | 12.4 | 3.5 | 3.13 | H5 | 6.5 | 6.6 | 3.28 | 5.52 | 5.75 |
| ICI97T-035H5 | 12.4 | 3.5 | 3.13 | H5 | 6.5 | 6.6 | 3.28 | 5.52 | 5.75 |
| ICI97T-052H6 | 15.4 | 5.2 | 5.21 | H6 | 10.5 | 6.2 | 6.04 | 4.75 | 5.3 |

INDUCTORS AND TRANSFORMERS FROM INTERNATIONAL COIL, INC.

| PART NUMBER | REFERENCE OPERATING VALUES | | | | DESIGN CONTROL VALUES | | | | | |
|-------------------------------------------------------------|----------------------------|----------|------------|-------|------------------------|------------------|---------------------|---------|-----------|---------------|
| | INDUCTANCE TYPICAL | IDC/Amps | ET/V-u sec | | ENERGY STORAGE u J MIN | INDUCTANCE NO DC | 50KHz TEST mV NO DC | DCR MAX | SIZE CODE | LEAD DIAMETER |
| | | | 20KHz | 40KHz | | | | | | |
| ICI98T SERIES HIGH AND LOW CURRENT COUPLED INDUCTORS | | | | | | | | | | |
| ICI98T-1703 | 17 | 17 | 190 | 130 | 2460 | 40 | 140 | 0.0065 | 3 | 0.081 |
| ICI98T-3204 | 32 | 16 | 290 | 200 | 4100 | 70.7 | 270 | 0.0092 | 4 | 0.081 |
| ICI98T-6005 | 60 | 16 | 390 | 270 | 7700 | 120 | 470 | 0.012 | 5 | 0.081 |
| ICI98T-1401 | 14 | 10 | 135 | 95 | 700 | 28.5 | 73 | 0.009 | 1 | 0.057 |
| ICI98T-2302 | 23 | 11 | 170 | 120 | 1400 | 43.5 | 130 | 0.012 | 2 | 0.057 |
| ICI98T-4303 | 43 | 10 | 280 | 195 | 2150 | 85.5 | 210 | 0.018 | 3 | 0.057 |
| ICI98T-9004 | 90 | 10 | 430 | 300 | 4500 | 158 | 420 | 0.028 | 4 | 0.057 |
| ICI98T-1445 | 144 | 10 | 570 | 400 | 7200 | 262 | 700 | 0.032 | 5 | 0.057 |
| ICI98T-3201 | 32 | 6.6 | 200 | 140 | 700 | 60.5 | 110 | 0.025 | 1 | 0.04 |
| ICI98T-5202 | 52 | 7 | 230 | 160 | 1275 | 92 | 190 | 0.032 | 2 | 0.04 |
| ICI98T-9803 | 98 | 6 | 400 | 280 | 1765 | 188 | 310 | 0.048 | 3 | 0.04 |
| ICI98T-1754 | 175 | 6 | 620 | 425 | 3150 | 315 | 560 | 0.068 | 4 | 0.04 |
| ICI98T-3355 | 335 | 6 | 840 | 580 | 6030 | 571 | 1000 | 0.095 | 5 | 0.04 |
| ICI98T-4013 | 400 | 3.6 | 600 | 420 | 2700 | 688 | 640 | 0.13 | 3 | 0.036 |


| PART NUMBER | REFERENCE VALUES | | | | CONTROL VALUES | | CALCULATION DATA | |
|--------------------------------------------------|------------------|----------|------------|------------------|----------------|---------|------------------|-------------|
| | IDC/Amp | L@DC/LDC | ET/V-u sec | Storage Capacity | LW/0 DC | DCR MAX | 100 GAUSS ET100 | 1 Amp DC,H1 |
| ICI99T INDUCTOR for HARRIS SEMI-CONDUCTOR | | | | | | | | |
| ICI99T-074D3 | 4.96 | 7.4 | 14.34 | 90.43 | 12.7 | 18.2 | 1.2 | 7.42 |

| PART NO. | IND.mH min | uH max | Rdc/ohm max | Rated Current A/rms |
|-----------------------------------------------|------------|--------|-------------|---------------------|
| ICI25EE SERIES COMMON MODE LINE FILTER | | | | |
| ICI25EE-36220A | 2x3.6 | 50 | 0.2 | 2 |
| ICI25EE-22312A | 2x22 | 500 | 0.6 | 1.2 |
| ICI25EE-90219A | 2x9 | 100 | 0.3 | 1.9 |
| ICI25EE-40308A | 2x40 | 500 | 1.5 | 0.8 |
| ICI25EE-99212A | 2x9.9 | 100 | 1 | 1.2 |


INDUCTORS AND TRANSFORMERS FROM INTERNATIONAL COIL, INC.

| PART NUMBER | Induc- tance ±10% at 1KHz | RDC MAX | I DC Cont.A | Temp Rise at IDC | Nominal Q At F KHz | | Nominal Self Reso- nant Fre- quency MHz | Outline Dimensions | | | | | Footprint | |
|---------------------------------------------|------------------------------------|---------|----------------|---------------------|--------------------|-----|--------------------------------------------------|--------------------|------|------|------|------|-----------|-----|
| ICIBI-1 SERIES BOBBIN TYPE INDUCTORS | | | | | | | | | | | | | | |
| | | | | | Q | F | | a | b | c | d | e | f | g |
| ICIBI1-2414-10013A | 10 | 0.007 | 13 | 20 | 54 | 50 | 20.7 | 27 | 24.4 | 14 | 1.3 | 4.5* | 23.9 | 2.6 |
| ICIBI1-2414-15012A | 15 | 0.009 | 12 | 25 | 42 | 50 | 12.7 | 27 | 24.4 | 14 | 1.3 | 4.5* | 23.9 | 2.6 |
| ICIBI1-2414-22011A | 22 | 0.011 | 11 | 27 | 64 | 100 | 9.3 | 27 | 24.4 | 14 | 1.3 | 4.5* | 23.9 | 2.6 |
| ICIBI1-2414-3309.3A | 33 | 0.015 | 9.3 | 25 | 27 | 50 | 9.1 | 27 | 24.4 | 14 | 1.3 | 4.5* | 23.9 | 2.6 |
| ICIBI1-2418-4708.3A | 47 | 0.019 | 8.3 | 25 | 40 | 100 | 6 | 27 | 24.4 | 18.5 | 1.3 | 4.5* | 23.9 | 2.6 |
| ICIBI1-2414-4708.5A | 47 | 0.021 | 8.5 | 26 | 33 | 100 | 6.7 | 26.8 | 24.4 | 14 | 1.2 | 4.5* | 23.8 | 2.4 |
| ICIBI1-2414-6806.2A | 68 | 0.032 | 6.2 | 27 | 32 | 100 | 5.3 | 26.5 | 24.4 | 14 | 1.08 | 4.5* | 23.7 | 2.1 |
| ICIBI1-2418-6807.3A | 68 | 0.022 | 7.3 | 27 | 45 | 100 | 5.3 | 27 | 24.4 | 18.5 | 1.3 | 4.5* | 23.9 | 2.6 |
| ICIBI1-2414-1015.4A | 100 | 0.042 | 5.4 | 27 | 24 | 100 | 4.6 | 26.4 | 24.4 | 14 | 1.02 | 4.5* | 23.6 | 2 |
| ICIBI1-2418-1016A | 100 | 0.033 | 6 | 29 | 37 | 100 | 3.9 | 26.8 | 24.4 | 18.5 | 1.2 | 4.5* | 23.8 | 2.4 |
| ICIBI1-3022-1017.8A | 100 | 0.04 | 7.8 | 28 | 34 | 50 | 3.3 | 32.4 | 29.8 | 21.8 | 1.3 | 5.1 | 29.3 | 2.6 |
| ICIBI1-2414-1514A | 150 | 0.069 | 4 | 26 | 24 | 50 | 3.4 | 26.2 | 24.4 | 14 | 0.9 | 4.5* | 23.5 | 1.8 |
| ICIBI1-2414-1514.9A | 150 | 0.051 | 4.9 | 27 | 34 | 50 | 2.9 | 26.4 | 24.4 | 18.5 | 1.02 | 4.5* | 23.6 | 2 |
| ICIBI1-3022-1516.5A | 150 | 0.042 | 6.5 | 29 | 46 | 100 | 2.4 | 32.2 | 29.8 | 21.8 | 1.2 | 5.1 | 29.2 | 2.4 |
| ICIBI1-2926-1517.3A | 150 | 0.036 | 7.5 | 29 | 42 | 50 | 3.2 | 32.4 | 29.8 | 26.5 | 1.3 | 5.1 | 29.3 | 2.6 |
| ICIBI1-2414-2213.5A | 220 | 0.096 | 3.5 | 29 | 22 | 50 | 2.8 | 26.1 | 24.4 | 14 | 0.85 | 4.5* | 23.5 | 1.7 |
| ICIBI1-2418-2214.1A | 220 | 0.073 | 4.1 | 25 | 33 | 100 | 2.3 | 26.3 | 24.4 | 18.5 | 0.97 | 4.5* | 23.6 | 1.9 |
| ICIBI1-3022-2215.5A | 220 | 0.062 | 5.5 | 27 | 30 | 50 | 2.2 | 32.1 | 29.8 | 21.8 | 1.14 | 5.1 | 29.1 | 2.2 |
| ICIBI1-3024-2216.3A | 220 | 0.05 | 6.3 | 27 | 47 | 100 | 1.8 | 32.4 | 29.8 | 26.5 | 1.3 | 5.1 | 29.3 | 2.6 |
| ICIBI1-2414-3013A | 300 | 0.14 | 3 | 23 | 26 | 50 | 2.6 | 25.9 | 24.4 | 14 | 0.75 | 4.5* | 23.4 | 1.5 |
| ICIBI1-2418-3013.5A | 300 | 0.1 | 3.5 | 25 | 37 | 50 | 2.2 | 26.2 | 24.4 | 18.5 | 0.9 | 4.5* | 23.5 | 1.8 |
| ICIBI1-3022-3015A | 300 | 0.08 | 5 | 29 | 28 | 50 | 1.7 | 31.8 | 29.8 | 21.8 | 1.02 | 5.1 | 29 | 2 |
| ICIBI1-3627-3017A | 300 | 0.054 | 7 | 28 | 43 | 50 | 1.4 | 39.4 | 36.8 | 27.1 | 1.3 | 6.3 | 36.3 | 2.6 |

INDUCTORS AND TRANSFORMERS FROM INTERNATIONAL COIL, INC.

| PART NUMBER | Inductance ±10% at 1KHz | RDC MAX | DC Cont.A | Temp Rise at IDC | Nominal Q At F KHz | | Nominal Self Reso- nant Fre- quency MHZ | Outline Dimensions | | | | | Footprint | |
|-------------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------|-----------|---------------------|--------------------|----|-----------------------------------------------------|--------------------|------|------|------|------|-----------|-----|
| ICIBI-2 SERIES BOBBIN TYPE INDUCTORS  | | | | | | | | | | | | | | |
| | | | | | Q | F | | a | b | c | d | e | f | g |
| ICIBI2-2414-3012.8A | 330 | 0.15 | 2.8 | 24 | 22 | 50 | 2.5 | 25.9 | 24.4 | 14 | 0.76 | 4.5* | 23.4 | 1.5 |
| ICIBI2-2418-3313.3A | 330 | 0.107 | 3.3 | 25 | 29 | 50 | 2 | 26.2 | 24.4 | 18.5 | 0.9 | 4.5* | 23.5 | 1.8 |
| ICIBI2-3022-3314.5A | 330 | 0.091 | 4.5 | 29 | 25 | 50 | 1.6 | 31.8 | 29.8 | 21.8 | 1.02 | 5.1 | 29 | 2 |
| ICIBI2-3026-3315.1A | 330 | 0.068 | 5.1 | 29 | 45 | 50 | 1.4 | 32.2 | 29.8 | 26.5 | 1.2 | 5.1 | 29.2 | 2.4 |
| ICIBI2-3727-3316.3A | 330 | 0.05 | 6.3 | 29 | 34 | 50 | 1.2 | 39.4 | 36.8 | 27.1 | 1.3 | 6.3 | 36.3 | 2.6 |
| ICIBI2-2414-4712.3A | 470 | 0.222 | 2.3 | 28 | 25 | 50 | 2 | 25.7 | 24.4 | 14 | 0.67 | 4.5* | 23.3 | 1.3 |
| ICIBI2-2418-4712.7A | 470 | 0.149 | 2.7 | 24 | 24 | 50 | 1.6 | 26.1 | 24.4 | 18.5 | 0.85 | 4.5* | 23.5 | 1.7 |
| ICIBI2-3022-4714A | 470 | 0.125 | 4 | 29 | 60 | 50 | 1.4 | 31.7 | 29.8 | 21.8 | 0.97 | 5.1 | 29 | 1.9 |
| ICIBI2-3026-4714.8A | 470 | 0.094 | 4.8 | 27 | 60 | 50 | 1.2 | 31.9 | 29.8 | 26.5 | 1.08 | 5.1 | 29.1 | 2.1 |
| ICIBI2-3727-4715.9A | 470 | 0.06 | 5.9 | 29 | 23 | 50 | 1 | 39.4 | 36.8 | 27.1 | 1.3 | 6.3 | 36.3 | 2.6 |
| ICIBI2-2414-6812A | 680 | 0.276 | 2 | 25 | 28 | 50 | 1.6 | 25.7 | 24.4 | 14 | 0.67 | 4.5* | 23.3 | 1.3 |
| ICIBI2-2418-6812.2A | 680 | 0.226 | 2.2 | 28 | 60 | 10 | 1.3 | 25.9 | 24.4 | 18.5 | 0.75 | 4.5* | 23.4 | 1.5 |
| ICIBI2-3022-6813.1A | 680 | 0.173 | 3.1 | 27 | 42 | 50 | 1 | 31.6 | 29.8 | 21.8 | 0.9 | 5.1 | 28.9 | 1.8 |
| ICIBI2-3026-6814A | 680 | 0.128 | 4 | 27 | 43 | 50 | 1.1 | 31.8 | 29.8 | 26.5 | 1.02 | 5.1 | 29 | 2 |
| ICIBI2-3727-6814.7A | 680 | 0.101 | 4.7 | 29 | 30 | 50 | 0.9 | 39.2 | 36.8 | 27.1 | 1.2 | 6.3 | 36.2 | 2.4 |
| ICIBI2-2414-1021.6A | 1.0mH | 0.419 | 1.6 | 24 | 35 | 50 | 1.4 | 25.6 | 24.4 | 14 | 0.6 | 4.5* | 23.2 | 1.2 |
| ICIBI2-2418-1021.7A | 1.0mH | 0.336 | 1.7 | 26 | 33 | 50 | 1.2 | 25.7 | 24.4 | 18.5 | 0.67 | 4.5* | 23.3 | 1.3 |
| ICIBI2-3022-1022.4A | 1.0mH | 0.277 | 2.4 | 28 | 49 | 50 | 1 | 31.4 | 29.8 | 21.8 | 0.79 | 5.1 | 28.8 | 1.5 |
| ICIBI2-3026-1023.1A | 1.0mH | 0.194 | 3.1 | 29 | 49 | 10 | 0.9 | 31.6 | 29.8 | 26.5 | 0.92 | 5.1 | 28.9 | 1.8 |
| ICIBI2-3727-1024A | 1.0mH | 0.18 | 40 | 30 | 34 | 50 | 0.8 | 38.8 | 36.8 | 27.1 | 1.02 | 6.3 | 36 | 2 |
| ICIBI2-2414-1521.3A | 1.5mH | 0.63 | 1.3 | 27 | 34 | 50 | 1 | 25.5 | 24.4 | 14 | 0.54 | 4.5* | 23.1 | 1 |
| ICIBI2-2418-1521.4A | 1.5mH | 0.518 | 1.4 | 26 | 47 | 50 | 0.8 | 25.6 | 24.4 | 18.5 | 0.6 | 4.5* | 23.2 | 1.2 |
| ICIBI2-3022-1521.7A | 1.5mH | 0.374 | 1.7 | 26 | 28 | 50 | 0.7 | 31.3 | 29.8 | 21.8 | 0.75 | 5.1 | 28.8 | 1.5 |

INDUCTORS AND TRANSFORMERS FROM INTERNATIONAL COIL, INC.

| PART NUMBER | Inductance ±10% at 1KHz | RDC MAX | DC Cont.A | Temp Rise at IDC | Nominal Q At F KHz | | Nominal Self Reso- nant Fre- quency MHz | Outline Dimensions | | | | | Footprint | |
|------------------------------------------------------------------------------------------------------------------------|-------------------------------|---------|-----------|---------------------|--------------------|-----|-----------------------------------------------------|--------------------|------|------|------|------|-----------|-----|
| ICIBI-3 SERIES BOBBIN TYPE INDUCTORS  | | | | | | | | | | | | | | |
| | | | | | Q | F | | a | b | c | d | e | f | g |
| ICIBI3-3026-1522.5A | 1.5 | 0.304 | 2.5 | 28 | 32 | 50 | 0.7 | 31.5 | 29.8 | 26.5 | 0.85 | 5.1 | 28.9 | 1.7 |
| ICIBI3-3727-1523.3A | 1.5 | 0.196 | 3.3 | 30 | 22 | 50 | 0.7 | 38.8 | 36.8 | 27.1 | 1.02 | 6.3 | 36 | 2 |
| ICIBI3-2414-2220.9A | 2.2 | 0.916 | 0.9 | 25 | 43 | 50 | 0.9 | 25.3 | 24.4 | 14 | 0.48 | 4.5* | 23.1 | 0.9 |
| ICIBI3-2418-2221.2A | 2.2 | 0.649 | 1.2 | 25 | 33 | 50 | 0.7 | 25.6 | 24.4 | 18.5 | 0.6 | 4.5* | 23.2 | 1.2 |
| ICIBI3-3022-2221.4A | 2.2 | 0.622 | 1.4 | 27 | 33 | 50 | 0.6 | 31.1 | 29.8 | 21.8 | 0.67 | 5.1 | 28.7 | 1.3 |
| ICIBI3-3026-2222A | 2.2 | 0.486 | 2 | 29 | 21 | 100 | 0.6 | 31.4 | 29.8 | 26.5 | 0.79 | 5.1 | 28.8 | 1.5 |
| ICIBI3-3727-2222.7A | 2.2 | 0.317 | 2.7 | 28 | 21 | 100 | 0.6 | 38.6 | 36.8 | 27.1 | 0.92 | 6.3 | 35.9 | 1.8 |
| ICIBI3-2414-3320.7A | 3.3 | 1.428 | 0.7 | 22 | 45 | 50 | 0.8 | 25.2 | 24.4 | 14 | 0.43 | 4.5* | 23 | 0.8 |
| ICIBI3-2418-3321A | 3.3 | 1.992 | 1 | 26 | 20 | 50 | 0.7 | 25.5 | 24.4 | 18.5 | 0.54 | 4.5* | 23.1 | 1 |
| ICIBI3-3022-3321.2A | 3.3 | 0.861 | 1.2 | 26 | 20 | 50 | 0.5 | 31 | 29.8 | 21.8 | 0.6 | 5.1 | 28.6 | 1.2 |
| ICIBI3-3026-3321.6A | 3.3 | 0.712 | 1.6 | 28 | 38 | 50 | 0.4 | 31.1 | 29.8 | 26.5 | 0.67 | 5.1 | 28.7 | 1.3 |
| ICIBI3-3727-3322.1A | 3.3 | 0.55 | 2.1 | 29 | 22 | 50 | 0.4 | 38.5 | 36.8 | 27.1 | 0.85 | 6.3 | 35.9 | 1.7 |
| ICIBI3-2414-4720.6A | 4.7 | 0.2 | 0.6 | 27 | 60 | 50 | 0.6 | 25.2 | 24.4 | 14 | 0.39 | 4.5* | 23 | 0.7 |
| ICIBI3-2418-4720.8A | 4.7 | 1.436 | 0.8 | 26 | 65 | 50 | 0.5 | 25.3 | 24.4 | 18.5 | 0.48 | 4.5* | 23.1 | 0.9 |
| ICIBI3-3022-4720.9A | 4.7 | 1.25 | 0.9 | 28 | 57 | 10 | 0.5 | 30.9 | 29.8 | 21.8 | 0.54 | 5.1 | 28.5 | 1 |
| ICIBI3-3026-4721.2A | 4.7 | 1.038 | 1.2 | 28 | 50 | 10 | 0.4 | 31 | 29.8 | 26.5 | 0.6 | 5.1 | 28.6 | 1.2 |
| ICIBI3-3727-4721.8A | 4.7 | 0.68 | 1.8 | 29 | 54 | 10 | 0.3 | 38.3 | 36.8 | 27.1 | 0.75 | 6.3 | 35.8 | 1.5 |
| ICIBI3-2414-6820.5A | 6.8 | 2.81 | 0.5 | 24 | 50 | 50 | 0.5 | 25.2 | 24.4 | 14 | 0.39 | 4.5* | 23 | 0.7 |
| ICIBI3-2418-4720.7A | 6.8 | 2.214 | 0.7 | 25 | 47 | 50 | 0.4 | 25.2 | 24.4 | 18.5 | 0.43 | 4.5* | 23 | 0.8 |
| ICIBI3-2418-4720.7A | 6.8 | 2.214 | 0.7 | 25 | 47 | 50 | 0.4 | 25.2 | 24.4 | 18.5 | 0.43 | 4.5* | 23 | 0.8 |
| ICIBI3-3022-6820.8A | 6.8 | 1.884 | 0.8 | 26 | 30 | 50 | 0.4 | 30.7 | 29.8 | 21.8 | 0.48 | 5.1 | 28.5 | 0.9 |
| ICIBI3-3026-6821.2A | 6.8 | 1.278 | 1.2 | 28 | 20 | 50 | 0.3 | 31 | 29.8 | 26.5 | 0.6 | 5.1 | 28.6 | 1.2 |
| ICIBI3-3727-6821.4A | 6.8 | 0.943 | 1.4 | 29 | 17 | 50 | 0.3 | 38.3 | 36.8 | 27.1 | 0.75 | 6.3 | 35.8 | 1.5 |
| ICIBI3-3026-9021A | 9 | 1.95 | 1 | 28 | 33 | 50 | 0.2 | 30.9 | 29.8 | 26.5 | 0.54 | 5.1 | 28.5 | 1 |

INDUCTORS AND TRANSFORMERS FROM INTERNATIONAL COIL, INC.

| PART NUMBER | Inductance ±10% at 1KHz | RDC MAX | I DC Cont.A | Temp Rise at IDC | Nominal Q At F KHz | | Nominal Self Reso- nant Fre- quency MHz | Outline Dimensions | | | | | Footprint | |
|---------------------------------------------|-------------------------------|---------|----------------|---------------------|--------------------|----|-----------------------------------------------------|--------------------|------|------|------|------|-----------|-----|
| | | | | | Q | F | | a | b | c | d | e | f | g |
| ICIBI-4 SERIES BOBBIN TYPE INDUCTORS | | | | | | | | | | | | | | |
| ICIBI4-2414-1030.4A | 10 | 4.34 | 0.4 | 22 | 51 | 50 | 0.4 | 25.1 | 24.4 | 14 | 0.34 | 4.5* | 22.9 | 0.6 |
| ICIBI4-2418-1030.5A | 10 | 3.394 | 0.5 | 24 | 48 | 50 | 0.3 | 25.2 | 24.4 | 18.5 | 0.39 | 4.5* | 23 | 0.7 |
| ICIBI4-3022-1030.6A | 10 | 2.294 | 0.6 | 25 | 48 | 50 | 0.2 | 30.9 | 29.8 | 21.8 | 0.54 | 5.1 | 28.5 | 1 |
| ICIBI4-3026-1031A | 10 | 1.95 | 1 | 28 | 35 | 50 | 0.2 | 30.9 | 29.8 | 26.5 | 0.54 | 5.1 | 28.5 | 1 |
| ICIBI4-3026-1031A | 10 | 1.95 | 1 | 28 | 35 | 50 | 0.2 | 30.9 | 29.8 | 26.5 | 0.54 | 5.1 | 28.5 | 1 |
| ICIBI4-3727-1031.1A | 10 | 1.394 | 1.1 | 27 | 30 | 50 | 0.1 | 38.1 | 36.8 | 27.1 | 0.67 | 6.3 | 35.7 | 1.3 |
| ICIBI4-2418-1530.4A | 15 | 4.912 | 0.4 | 25 | 61 | 10 | 0.2 | 25.1 | 24.4 | 18.5 | 0.34 | 4.5* | 22.9 | 0.6 |
| ICIBI4-3022-1530.5A | 15 | 3.74 | 0.5 | 21 | 55 | 10 | 0.2 | 30.6 | 29.8 | 21.8 | 0.43 | 5.1 | 28.4 | 0.8 |
| ICIBI4-2418-3321A | 3.3 | 1.992 | 1 | 26 | 20 | 50 | 0.7 | 25.5 | 24.4 | 18.5 | 0.54 | 4.5* | 23.1 | 1 |
| ICIBI4-3022-3321.2A | 3.3 | 0.861 | 1.2 | 26 | 20 | 50 | 0.5 | 31 | 29.8 | 21.8 | 0.6 | 5.1 | 28.6 | 1.2 |
| ICIBI4-3026-3321.6A | 3.3 | 0.712 | 1.6 | 28 | 38 | 50 | 0.4 | 31.1 | 29.8 | 26.5 | 0.67 | 5.1 | 28.7 | 1.3 |
| ICIBI4-3727-3322.1A | 3.3 | 0.55 | 2.1 | 29 | 22 | 50 | 0.4 | 38.5 | 36.8 | 27.1 | 0.85 | 6.3 | 35.9 | 1.7 |
| ICIBI4-2414-4720.6A | 4.7 | 0.2 | 0.6 | 27 | 60 | 50 | 0.6 | 25.2 | 24.4 | 14 | 0.39 | 4.5* | 23 | 0.7 |
| ICIBI4-2418-4720.8A | 4.7 | 1.436 | 0.8 | 26 | 65 | 50 | 0.5 | 25.3 | 24.4 | 18.5 | 0.48 | 4.5* | 23.1 | 0.9 |
| ICIBI4-3022-4720.9A | 4.7 | 1.25 | 0.9 | 28 | 57 | 10 | 0.5 | 30.9 | 29.8 | 21.8 | 0.54 | 5.1 | 28.5 | 1 |
| ICIBI4-3026-4721.2A | 4.7 | 1.038 | 1.2 | 28 | 50 | 10 | 0.4 | 31 | 29.8 | 26.5 | 0.6 | 5.1 | 28.6 | 1.2 |
| ICIBI4-3727-4721.8A | 4.7 | 0.68 | 1.8 | 29 | 54 | 10 | 0.3 | 38.3 | 36.8 | 27.1 | 0.75 | 6.3 | 35.8 | 1.5 |
| ICIBI4-2414-6820.5A | 6.8 | 2.81 | 0.5 | 24 | 50 | 50 | 0.5 | 25.2 | 24.4 | 14 | 0.39 | 4.5* | 23 | 0.7 |
| ICIBI4-2418-4720.7A | 6.8 | 2.214 | 0.7 | 25 | 47 | 50 | 0.4 | 25.2 | 24.4 | 18.5 | 0.43 | 4.5* | 23 | 0.8 |
| ICIBI4-2418-4720.7A | 6.8 | 2.214 | 0.7 | 25 | 47 | 50 | 0.4 | 25.2 | 24.4 | 18.5 | 0.43 | 4.5* | 23 | 0.8 |
| ICIBI4-3022-6820.8A | 6.8 | 1.884 | 0.8 | 26 | 30 | 50 | 0.4 | 30.7 | 29.8 | 21.8 | 0.48 | 5.1 | 28.5 | 0.9 |
| ICIBI4-3026-6821.2A | 6.8 | 1.278 | 1.2 | 28 | 20 | 50 | 0.3 | 31 | 29.8 | 26.5 | 0.6 | 5.1 | 28.6 | 1.2 |
| ICIBI4-3727-6821.4A | 6.8 | 0.943 | 1.4 | 29 | 17 | 50 | 0.3 | 38.3 | 36.8 | 27.1 | 0.75 | 6.3 | 35.8 | 1.5 |
| ICIBI4-3026-9021A | 9 | 1.95 | 1 | 28 | 33 | 50 | 0.2 | 30.9 | 29.8 | 26.5 | 0.54 | 5.1 | 28.5 | 1 |